

Avala Hybrid Planks

SPC Rigid Core Flooring



The latest generation of Hybrid Flooring



CERTIFIED BY
SCS Global Services



Lifetime Structure
Warranty



TOPDECK FLOORING

- Avala Hybrid Planks / SCP Rigid Core Flooring -



Pebble Grey

1601 Pebble Grey



Orchid Ash

1602 Orchid Ash

- Avala Hybrid Planks / SCP Rigid Core Flooring -



Stamford Oak

1603 **Stamford Oak**



Coastal Beige

1604 **Coastal Beige**

- Avala Hybrid Planks / SCP Rigid Core Flooring -



Prague Oak

1605 **Prague Oak**



Moschino

1606 **Moschino**

- Avala Hybrid Planks / SCP Rigid Core Flooring -



Spotted Gum

1607 **Spotted Gum**



Blackbutt

1608 **Blackbutt**

- Avala Hybrid Planks / SCP Rigid Core Flooring -



Jarrah

1609 Jarrah



Tas Oak

1610 Tas Oak

AVALA HYBRID PLANKS, represents the latest generation of Hybrid Flooring, utilizes advanced manufacturing techniques which develops multi-layer rigid composite core planks (RCP). It is truly waterproof due to its solid core construction and high density, which makes it more indentation resistant. The enhanced multi-layer rigid core constructions also gives an excellent performance characteristic with dimensionally little or no movement.

For decoration, AVALA Hybrid's 0.5mm wear layer and printed visual décor provides realistic timber textures and colors which feels like authentic hardwood. For noise reduction, each plank is attached with an acoustic cross-linked IXPE foam layer, which ranks the floor as AAAC 5 Star Acoustic Rating.



AVALA HYBRID PLANKS TECHNICAL SPECIFICATIONS



TYPE

Avala Hybrid Planks

DIMENSIONS

1524mmx183mmx6.5mm
(5/0.5mm SPC + 1.5mm IXPE)

BOX CONTAINS

8 Planks = 2.231m²/box

INSTALLATION METHOD

Floating Floor (Licensed Click System)

SLIP RATING

AS4586 (2013) Slip Resistance Classification of New Pedestrian Surface Materials
Appendix A - Wet Pendulum Test
Achieved a pass of P4

FIRE RATING

Critical Heat/Radiant Flux (CHF)
Pass the AS ISO 9239.1 Standard as required by the Australian National Construction Code

ACOUSTIC RATING

Achieved AAAC 5 Star Acoustic Rating

ENVIRONMENTAL & QUALITY CERTIFICATES

VOC E0 (Volatile Organic Compound)
ISO9000 Quality Control System
ISO14000 Environment Control System

STRUCTURAL WARRANTY

Life Time Structure Warranty

VINYL WEAR LAYER

Hardened vinyl wear layer provides excellent resistance to scuffs and abrasions.

LUXURY RIGID CORE

100% phthalate-free extruded closed-cell core provides exceptional rigidity, dimensional stability, and anti-telegraphing performance.

QUIET INTEGRATED SOUND REDUCTION UNDERLAYMENT

Bonded cross-linked underlayment minimizes impact and transmitted sound, provides underfoot warmth and comfort, and mitigates subfloor imperfections.

URETHANE WITH CERAMIC BEAD FINISH

UV cured urethane and ceramic bead top coating for enhanced durability, stain resistance, and easy care and maintenance.

HD DECORATIVE FILM

High definition film prints create vivid, natural wood, stone, and abstract looks.

CLICK LOCKING SYSTEM

Innovative locking system enables quick, easy, hassle-free installation.



quick and easy installation



slip resistance



glue-free installation



easy maintenance



abrasion resistance



color fastness to light



resistance to cigarette ash



warm to the touch



resistance to water



indentation resistance



static resistance



high elasticity

Note: Colour grain & feature patterns may vary from the actual product to the electronic and printed media. For detail maintenance & installation guidelines please refer to the website.



*Quality is our attitude, as we are
always striving to meet and exceed
our customers expectations.*



TOPDECK FLOORING

Topdeck International Pty Ltd
16 Salisbury Street, Silverwater, NSW 2128 Australia
Phone: 02-9748 2288
Email: info@topdeckflooring.com.au

Proud to be a Member of the

atfa
Australian timber flooring association